NASA/ADS

New developments in the protoMIRAX balloon telescope

Show affiliations

Braga, Joao; D'Amico, Flavio; Rodrigues, Barbara; Avila, Manuel; Santiago, Valdivino, Jr.; Mattiello-Francisco, Fatima; Varela, Ricardo; Mejia, Jorge

The protoMIRAX X-ray imaging telescope is a balloon-borne experiment under development at INPE as a pathfinder for the MIRAX (Monitor Imageador de Raios X) satellite mission. The main objective of protoMIRAX is to test several subsystems of MIRAX in a near-space environment, including hardware components, software for data acquisition and handling, and the implementation of novel coded-aperture techniques. A modified and space-qualified pro-toMIRAX camera will be one of the MIRAX instruments onboard the Lattes scientific satellite, scheduled to be launched in 2015 as part of the Brazilian space program. The experiment con-sists essentially in an X-ray (30-200 keV) coded-aperture imager which employs a square array of 196 10mm x 10mm x 2mm CdZnTe (CZT) detectors. A collimator defines a fully-coded field-of-view of 200 x 200, with 40 x 40 of full sensitivity. In this paper we show new detailed simulations of the protoMIRAX camera background both at balloon-altitudes and at equatorial LEO using the GEANT-based MGGPOD package. We show results of simulations that identify the optimum mask pattern to use in this experiment in order to achieve the best combination of signal-to-noise ratio and angular resolution. We also present calibration results of the CZT detectors in the lab.

Publication:

38th COSPAR Scientific Assembly. Held 18-15 July 2010, in Bremen, Germany, p.9

Pub Date:

2010

Bibcode:

2010cosp...38.4071B

Comments:

Symposium PSB, session 1, paper number PSB1-0026-10 (Oral) (solicited)

Feedback/Corrections? (/feedback/correctabstract?bibcode=2010cosp...38.4071B)